

# SINGLE SOLAR CIRCULATOR PUMP

## Technical datasheet Nr 19

### DESCRIPTION:


- High efficiency
- Temperature: -10 to 110°C
- Built-in motor protection
- Control input 0-10 V (depending on the application)
- Suitable for water glycol mixtures up to 50% concentration
- 2 two-piece fittings (except for flange version)




### TECHNICAL SPECIFICATIONS:

Reference	Type	Transfer module* flat/tube (m <sup>2</sup> )	Connection	Nominal pressure (bar)	Body	Main supply	Absorbed current (A)
40030410005	Stratos 25/1-6	- / -	1"1/2 - 1"	10	Grey cast iron	1~230V 50Hz	0.78
40030410006	Stratos 25/1-8	- / -	1"1/2 - 1"	10	Grey cast iron	1~230V 50Hz	1.2
40030410007	Stratos 25/1-10	- / -	1"1/2 - 1"	10	Grey cast iron	1~230V 50Hz	1.3
40030400509	Stratos 30/1-10	80 / 20	2" - 1"1/4	10	Grey cast iron	1~230V 50Hz	1.3
40030400510	Stratos 30/1-12	160 / 100	2" - 1"1/4	10	Grey cast iron	1~230V 50Hz	1.37
40030410008	Stratos 32/1-10	- / -	Flange DN32	10	Grey cast iron	1~230V 50Hz	1.3
40030410009	Stratos 32/1-12	- / -	Flange DN32	10	Grey cast iron	1~230V 50Hz	1.37
40030410010	Stratos 40/1-8	- / -	Flange DN40	10	Grey cast iron	1~230V 50Hz	1.37
40030410011	Stratos 40/1-12	- / -	Flange DN40	10	Grey cast iron	1~230V 50Hz	2.05
40030410524	Stratos 50/1-12	- / 180	Flange DN50	10	Grey cast iron	1~230V 50Hz	2.6
40030410513	Stratos 80/1-12	- / 350	Flange DN80	10	Grey cast iron	1~230V 50Hz	6.8


\* Information for reference only. It is imperative to check the available head against the height of the installation.




Reference: 40030410005




Reference: 40030410006




Reference: 40030410007




Reference: 40030400509




Reference: 40030400510




Reference: 40030410008




Reference: 40030410009




Reference: 40030410010



Reference: 40030410011



Reference: 40030410524



Reference: 40030410513